



12V GEL Battery (CNJ-HTR series) ~High Temperature Resistance~



- ※ Higher Temperature Resistance than normal Solar GEL Battery
- ※ Advance Plate & Grid design. Enhance the corrosion resistance. Increasing the cycle life of the battery
- ※ Using Modified GEL Electrolyte and Charge Acceptance to improve high temperature battery performance
- ※ TESTED and PASS the test requirement for high temperature battery (at 45 C and 60 C)
- ※ Valve Regulated sealed structure, the safe and explosion-proof vent system solved battery seal maintenance free
- ※ With super over charge and deep discharge capacity
- ※ Unique sealed insulated output devices, solve the short-circuit and wet corrosion of battery, even the corrosion problem underwater short-term use, greatly reduce the battery maintenance frequency
- ※ Battery design lifetime : 12 years
- ※ Water proof: IP 65

Battery list

Type	Rated Voltage (V)	Rated Capacity at 10h rate (Ah)	The Maximum Dimension(mm)				Weight (kg)	Connection
			L	W	H1	H2		
CNJ24	12	24	164	124	176	176	9.0	Bolt or Cable
CNJ38	12	38	195	165	175	175	12.5	
CNJ55	12	55	260	165	170	170	16.5	
CNJ65	12	65	351	165	180	180	22.0	
CNJ80	12	80	331	172	215	218	24.5	
CNJ90	12	90	331	172	215	218	27.0	
CNJ100	12	100	331	172	215	218	29.5	
CNJ120	12	120	407	172	233	259	35.5	
CNJ135	12	135	341	173	258	283	41.5	
CNJ140	12	140	360	172	240	240	42.0	
CNJ150	12	150	483	170	240	240	42.5	
CNJ200	12	200	522	240	214	244	62.0	
CNJ6200	6	200	260	180	270	271	30.5	
CNJ6260	6	260	341	180	270	273	42.0	